



**Properties**

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

**Standard Selection**

Voltage	120V-277V (non dimming)
Finish	Black
CCT	3000K

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- White

**CCT Options**

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
BCHW-15	H:14.6" W:8.3" E:3.8"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BCHW-24	H:24" W:8.3" E:3.8"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250

**Options**

- BBX-Backbox W/ 3/4" Conduit hole
- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming
- PC - Photo Control

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)