



Properties

Base Construction	Stainless Steel
Lens	Acrylic
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Black
CCT	3CCT - 3000K / 3500K / 4000K

Finish Options

 Black	 Bronze
 Brushed Nickel	 Gold/Brass
 ORB	 White

CCT Options

CCT	2700K/3500k/3CCT
-----	------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
BCJ-12	H:11.8" W:6.1" E:4.35"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BCJ-18	H:18" W:6" E:4"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
BCJ-24	H:24" W:6" E:4"	15/23/30	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990/3900
BCJ-30	H:30" W:6" E:4"	20/28/40	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3640/5200

Options

- BBX-Backbox W/ 3/4" Conduit hole
- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming
- PC - Photo Control

Not seeing what you're looking for?

Contact us!

info@asllighting.com