



## **Properties**

| Base Construction | Steel<br>Acrylic |  |
|-------------------|------------------|--|
| Lens              |                  |  |
| Application       | Sconce           |  |
| Location          | Wet              |  |
| CRI               | 80               |  |
| Life Hours        | 50,000           |  |
| Light Source      | Integrated LED   |  |

## Standard Selection

| Voltage        | 120V (non dimming)            |  |  |
|----------------|-------------------------------|--|--|
| Finish         | Brushed Nickel                |  |  |
| сст            | 3000K                         |  |  |
| Finish Options |                               |  |  |
| Black          | Bronze                        |  |  |
| Brushed Nickel | Gold/Brass                    |  |  |
| ORB            | White                         |  |  |
| CCT Options    |                               |  |  |
| ССТ            | 2700K/3000K/3500k/4000K/5000K |  |  |

| Options |   |         |  |           |
|---------|---|---------|--|-----------|
| Size    | Dimensions                                      | Wattage | Voltage  | Lumens    |
| BCO-10  | H:10" W:6.5" E:4.5"                             | 10/15   | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950 |
|         | bancy Sensor<br>ccupancy Sensor Step<br>Control | Dimming | Not seeing what you're loo<br>Contact us!<br>info@asllighting.com  | king for? |

© Copyright © 2025 ASL Lighting Inc. All rights reserved.

asllighting.com