



ADA Compliant

Properties

Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	3000K

Finish Options

<input type="checkbox"/> Black	<input type="checkbox"/> Brushed Nickel
<input type="checkbox"/> Gold/Brass	<input type="checkbox"/> ORB
<input type="checkbox"/> White	

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
BCR-12	H:12" W:5.5" E:5"	6	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	780
BCR-16	H:16" W:6.5" E:6"	9	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1170
BCR-20	H:20" W:7.5" E:7"	14	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1820

Not seeing what you're looking for?

Contact us!

info@asllighting.com