



ADA Compliant

Properties

| | |
|-------------------|----------------|
| Base Construction | Steel |
| Lens | Acrylic |
| Application | Sconce |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish | Brushed Nickel |
| CCT | 3000K |

Finish Options

| | |
|----------------|------------|
| Black | Bronze |
| Brushed Nickel | Gold/Brass |
| ORB | White |

CCT Options

| | |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|------------------|----------|--|----------------|
| BCRC-12 | H:12" W:10" E:4" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |

Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!
info@asllighting.com