



**Properties**

|                          |                   |
|--------------------------|-------------------|
| <b>Base Construction</b> | Cold-rolled Steel |
| <b>Lens</b>              | Acrylic           |
| <b>Application</b>       | Sconce            |
| <b>Location</b>          | Damp              |
| <b>CRI</b>               | 80                |
| <b>Life Hours</b>        | 50,000            |
| <b>Light Source</b>      | Integrated LED    |

**Standard Selection**

|                |                         |
|----------------|-------------------------|
| <b>Voltage</b> | 120V-277V (non dimming) |
| <b>Finish</b>  | Brushed Nickel          |
| <b>CCT</b>     | 3000K                   |

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

|            |                               |
|------------|-------------------------------|
| <b>CCT</b> | 2700K/3000K/3500k/4000K/5000K |
|------------|-------------------------------|

**Options**

| Size    | Dimensions            | Wattage | Voltage  | Lumens |
|---------|-----------------------|---------|--|--------|
| BCRK-13 | H:12.8" W:4.3" E:3.5" | 9       | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1170   |

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)