



Properties

Base Construction	Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	ORB

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT	2700K/3500k/4000K/5000K
------------	-------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
BSK-15	H:15" W:9" E:4"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) DVD (120V-277V 0-10 dimming)	1300/1950/2600
BSK-18	H:18" W:9" E:4"	10/15/20	DVD (120V-277V 0-10 dimming) / ND (120V (non dimming)) TD (120V Triac dimming)	1300/1950/2600
BSK-26	H:26" W:9" E:4"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) DVD (120V-277V 0-10 dimming)	1950/2600/3250

Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!
info@asllighting.com