



Properties

| | |
|-------------------|----------------|
| Base Construction | Steel |
| Lens | Acrylic |
| Application | Sconce |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish | ORB |
| CCT | 3000K |

Finish Options

| | |
|----------------|------------|
| Black | Bronze |
| Brushed Nickel | Gold/Brass |
| ORB | White |

CCT Options

| | |
|-----|-------------------------|
| CCT | 2700K/3500k/4000K/5000K |
|-----|-------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|--------|-----------------|----------|---|----------------|
| BSK-15 | H:15" W:9" E:4" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming) DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |
| BSK-18 | H:18" W:9" E:4" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming) DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |
| BSK-26 | H:26" W:9" E:4" | 15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming) DVD (120V-277V 0-10 dimming) | 1950/2600/3250 |

Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you’re looking for?

Contact us!
info@asllighting.com