



### Properties

|                          |                 |
|--------------------------|-----------------|
| <b>Base Construction</b> | Stainless Steel |
| <b>Lens</b>              | Acrylic         |
| <b>Application</b>       | Sconce          |
| <b>Location</b>          | Damp            |
| <b>CRI</b>               | 80              |
| <b>Life Hours</b>        | 50,000          |
| <b>Light Source</b>      | Integrated LED  |

### Standard Selection

|                |                    |
|----------------|--------------------|
| <b>Voltage</b> | 120V (non dimming) |
| <b>Finish</b>  | Brushed Nickel     |
| <b>CCT</b>     | 3000K              |

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

|            |                               |
|------------|-------------------------------|
| <b>CCT</b> | 2700K/3000K/3500k/4000K/5000K |
|------------|-------------------------------|

### Options

| Size   | Dimensions      | Wattage  | Voltage  | Lumens         |
|--------|-----------------|----------|--|----------------|
| BSL-12 | H:12" W:6" E:4" | 10/15    | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950      |
| BSL-15 | H:15" W:6" E:4" | 15/20/25 | DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)<br>ND (120V (non dimming)) / TD (120V Triac dimming) | 1950/2600/3250 |
| BSL-18 | H:18" W:6" E:4" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3250/3900 |
| BSL-24 | H:24" W:6" E:4" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3250/3900 |
| BSL-30 | H:30" W:6" E:4" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3250/3900 |
| BSL-42 | H:42" W:6" E:4" | 30/35/40 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3900/4550/5200 |

## Options

BBX-Backbox W/ 3/4" Conduit hole

EMG – Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

PC - Photo Control

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)