



Properties

| | |
|-------------------|----------------|
| Base Construction | Steel |
| Lens | Acrylic |
| Application | Sconce |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish | Brushed Nickel |

Finish Options

| | |
|--|--|
|  Black |  Bronze |
|  Brushed Nickel |  Gold/Brass |
|  ORB |  White |

CCT Options

| | |
|-----|-------------------------|
| CCT | 2700K/3500k/4000K/5000K |
|-----|-------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|------------------|----------|---|----------------|
| BSNA-10 | H:11" W:10" E:4" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming) DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |
| BSNA-14 | H:16" W:16" E:4" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming) DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |

Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com