



### Properties

<b>Base Construction</b>	Cold-rolled Steel
<b>Lens</b>	Acrylic
<b>Application</b>	Sconce
<b>Location</b>	Damp
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED

### Standard Selection

<b>Voltage</b>	120V (non dimming)
<b>Finish</b>	Brushed Nickel
<b>CCT</b>	3000K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

<b>CCT</b>	2700K/3000K/3500k/4000K/5000K
------------	-------------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
BST-12	W:12.2" H:5.5" E:4"	10/14	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) ND (120V (non dimming)) / TD (120V Triac dimming)	1300/1820
BST-18	W:18.2" H:5.5" E:4"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BST-25	W:24.5" H:5.5" E:4"	15/23	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990
BST-36	W:36.5" H:5.5" E:4"	20/25/36	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/4680
BST-48	W:48.5" H:5.5" E:4"	20/35/46	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/4550/5980

### Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

### Not seeing what you're looking for?

Contact us!  
[info@asllighting.com](mailto:info@asllighting.com)