



**Properties**

<b>Base Construction</b>	Aluminum
<b>Lens</b>	Acrylic
<b>Application</b>	Pendant
<b>Location</b>	Dry
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED

**Standard Selection**

<b>Voltage</b>	120V-277V (non dimming)
<b>Finish</b>	White
<b>CCT</b>	4000K

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

<b>CCT</b>	3000K/3500k/4000K/5000K
------------	-------------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
C2105-23	D:23.6" H:1.4" W:1.3" MH:59"	32	DV (120V-277V (non dimming))	4160
C2105-35	D:35.4" H:1.4" W:1.3" MH:59"	40	DV (120V-277V (non dimming))	5200
C2105-47	D:47" H:1.4" W:1.3" MH:59"	70	DV (120V-277V (non dimming))	9100
C2105-59	D:59" H:1.4" W:1.3" MH:59"	80	DV (120V-277V (non dimming))	10400

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)