



Properties

| | |
|--------------------------|------------------|
| Base Construction | Aluminum |
| Lens | Polyethylene |
| Application | Pendant |
| Location | Dry |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |
| Light Direction | O OUTER EMITTING |

Standard Selection

| | |
|----------------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | White |
| CCT | 4000K |

Finish Options

White

CCT Options

| | |
|------------|-------------------------|
| CCT | 3000K/3500k/4000K/5000K |
|------------|-------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|----------|-----------------------|---------|------------------------------|--------|
| C2106-15 | D:15.7" H:2.6" MH:59" | 25 | DV (120V-277V (non dimming)) | 3250 |
| C2106-23 | D:23" H:2.6" MH:59" | 36 | DV (120V-277V (non dimming)) | 4680 |
| C2106-35 | D:35" H:2.6" MH:59" | 60 | DV (120V-277V (non dimming)) | 7800 |
| C2106-47 | D:47" H:2.6" MH:59" | 80 | DV (120V-277V (non dimming)) | 10400 |
| C2106-59 | D:59" H:2.6" MH:59" | 100 | DV (120V-277V (non dimming)) | 13000 |
| C2106-70 | D:70" H:2.6" MH:59" | 120 | DV (120V-277V (non dimming)) | 15600 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com