



**Properties**

<b>Base Construction</b>	Aluminum
<b>Lens</b>	Acrylic
<b>Application</b>	Pendant
<b>Location</b>	Dry
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED
<b>Light Direction</b>	O OUTER EMITTING

**Standard Selection**

<b>Voltage</b>	120V-277V (non dimming)
<b>Finish</b>	White
<b>CCT</b>	4000K

**Finish Options**

White

**CCT Options**

<b>CCT</b>	3000K/3500k/4000K/5000K
------------	-------------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
C2107-15	D:15.7" H:2.8" MH:59"	15	DV (120V-277V (non dimming))	1950
C2107-23	D:23" H:2.8" MH:59"	25	DV (120V-277V (non dimming))	3250
C2107-31	D:31" H:2.8" MH:59"	35	DV (120V-277V (non dimming))	4550
C2107-39	D:39.4" H:2.8" MH:59"	45	DV (120V-277V (non dimming))	5850
C2107-47	D:47" H:2.8" MH:59"	50	DV (120V-277V (non dimming))	6500
C2107-59	D:59" H:2.8" MH:59"	60	DV (120V-277V (non dimming))	7800

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)