



**Properties**

|                   |                |
|-------------------|----------------|
| Base Construction | Aluminum       |
| Lens              | Silicon        |
| Application       | Flush Mount    |
| Location          | Damp           |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |
| Light Direction   | 300            |

**Standard Selection**

|         |                        |
|---------|------------------------|
| Voltage | 120V-277V 0-10 dimming |
| Finish  | White                  |
| CCT     | 4000K                  |

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

|     |                   |
|-----|-------------------|
| CCT | 3000K/4000K/5000K |
|-----|-------------------|

**Options**

| Size     | Dimensions     | Wattage | Voltage                      | Lumens |
|----------|----------------|---------|------------------------------|--------|
| C2113-12 | D:11.8" H:0.7" | 32      | DVD (120V-277V 0-10 dimming) | 4160   |
| C2113-16 | D:15.7" H:0.7" | 45      | DVD (120V-277V 0-10 dimming) | 5850   |
| C2113-23 | D:23" H:0.7"   | 60      | DVD (120V-277V 0-10 dimming) | 7800   |
| C2113-35 | D:35" H:0.7"   | 100     | DVD (120V-277V 0-10 dimming) | 13000  |
| C2113-47 | D:47" H:0.7"   | 135     | DVD (120V-277V 0-10 dimming) | 17550  |

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)