



**Properties**

<b>Base Construction</b>	Aluminum
<b>Lens</b>	Silicon
<b>Application</b>	Flush Mount
<b>Location</b>	Damp
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED
<b>Light Direction</b>	300

**Standard Selection**

<b>Voltage</b>	120V-277V 0-10 dimming
<b>Finish</b>	White
<b>CCT</b>	4000K

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

<b>CCT</b>	3000K/4000K/5000K
------------	-------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
C2113-12	D:11.8" H:0.7"	32	DVD (120V-277V 0-10 dimming)	4160
C2113-16	D:15.7" H:0.7"	45	DVD (120V-277V 0-10 dimming)	5850
C2113-23	D:23" H:0.7"	60	DVD (120V-277V 0-10 dimming)	7800
C2113-35	D:35" H:0.7"	100	DVD (120V-277V 0-10 dimming)	13000
C2113-47	D:47" H:0.7"	135	DVD (120V-277V 0-10 dimming)	17550

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)