



**Properties**

<b>Base Construction</b>	Aluminum
<b>Lens</b>	Silicon
<b>Application</b>	Flush Mount
<b>Location</b>	Damp
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED

**Standard Selection**

<b>Voltage</b>	120V-277V 0-10 dimming
<b>Finish</b>	White
<b>CCT</b>	4000K

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

<b>CCT</b>	3000K/4000K/5000K
------------	-------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
C2116-12	W:11.8" H:0.7" L:11.8"	50	DVD (120V-277V 0-10 dimming)	6500
C2116-16	W:15.7" H:0.7" L:15.7"	60	DVD (120V-277V 0-10 dimming)	7800
C2116-20	W:19.7" H:0.7" L:19.7"	90	DVD (120V-277V 0-10 dimming)	11700
C2116-35	L:35.4" H:0.7" W:19.7"	125	DVD (120V-277V 0-10 dimming)	16250
C2116-43	L:43.3" H:0.7" W:25.6"	150	DVD (120V-277V 0-10 dimming)	19500

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)