



**Properties**

<b>Base Construction</b>	Aluminum
<b>Lens</b>	Acrylic
<b>Application</b>	Pendant
<b>Location</b>	Dry
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED
<b>Light Direction</b>	DOWN

**Standard Selection**

<b>Voltage</b>	120V-277V (non dimming)
<b>Finish</b>	White
<b>CCT</b>	4000K

**Finish Options**

White

**CCT Options**

<b>CCT</b>	3000K/3500k/4000K/5000K
------------	-------------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
C2121-11	W:11.8" H:3" L:11.8" MH:59"	15	DV (120V-277V (non dimming))	1950
C2121-S23	W:23.6" H:3" L:23.6" MH:59"	40	DV (120V-277V (non dimming))	5200
C2121-23	W:23.6" H:3" L:47.2" MH:59"	80	DV (120V-277V (non dimming))	10400
C2121-47	W:47" H:3" L:47" MH:59"	160	DV (120V-277V (non dimming))	20800
C2121-94	L:94" H:3" W:47" MH:59"	320	DV (120V-277V (non dimming))	41600

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)