



Properties

| | |
|--------------------------|----------------|
| Base Construction | Aluminum |
| Lens | Acrylic |
| Application | Pendant |
| Location | Dry |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |
| Light Direction | DOWN |

Standard Selection

| | |
|----------------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | White |
| CCT | 4000K |

Finish Options

White

CCT Options

| | |
|------------|-------------------------|
| CCT | 3000K/3500k/4000K/5000K |
|------------|-------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|----------|---------------------------|---------|------------------------------|--------|
| C2122-16 | L:16.4" H:3" W:14" MH:59" | 25 | DV (120V-277V (non dimming)) | 3250 |
| C2122-20 | L:20" H:3" W:17" MH:59" | 40 | DV (120V-277V (non dimming)) | 5200 |
| C2122-30 | L:30" H:3" W:26" MH:59" | 90 | DV (120V-277V (non dimming)) | 11700 |
| C2122-40 | L:40" H:3" W:35" MH:59" | 180 | DV (120V-277V (non dimming)) | 23400 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com