



**Properties**

|                          |                |
|--------------------------|----------------|
| <b>Base Construction</b> | Aluminum       |
| <b>Lens</b>              | Acrylic        |
| <b>Application</b>       | Pendant        |
| <b>Location</b>          | Dry            |
| <b>CRI</b>               | 80             |
| <b>Life Hours</b>        | 50,000         |
| <b>Light Source</b>      | Integrated LED |
| <b>Light Direction</b>   | DOWN           |

**Standard Selection**

|                |                         |
|----------------|-------------------------|
| <b>Voltage</b> | 120V-277V (non dimming) |
| <b>Finish</b>  | White                   |
| <b>CCT</b>     | 4000K                   |

**Finish Options**

White

**CCT Options**

|            |                         |
|------------|-------------------------|
| <b>CCT</b> | 3000K/3500k/4000K/5000K |
|------------|-------------------------|

**Options**

| Size     | Dimensions              | Wattage | Voltage                      | Lumens |
|----------|-------------------------|---------|------------------------------|--------|
| C2123-18 | L:18" H:3" W:16" MH:59" | 25      | DV (120V-277V (non dimming)) | 3250   |
| C2123-23 | L:23" H:3" W:20" MH:59" | 40      | DV (120V-277V (non dimming)) | 5200   |
| C2123-35 | L:35" H:3" W:30" MH:59" | 90      | DV (120V-277V (non dimming)) | 11700  |
| C2123-47 | L:47" H:3" W:40" MH:59" | 180     | DV (120V-277V (non dimming)) | 23400  |

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)