



**Properties**

<b>Base Construction</b>	Aluminum
<b>Lens</b>	Acrylic
<b>Application</b>	Pendant
<b>Location</b>	Dry
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED

**Standard Selection**

<b>Voltage</b>	120V-277V (non dimming)
<b>Finish</b>	ASL-002 122
<b>CCT</b>	4000K

**Finish Options**

- |                                      |                                      |
|--------------------------------------|--------------------------------------|
| <input type="checkbox"/> ASL-001 141 | <input type="checkbox"/> ASL-002 122 |
| <input type="checkbox"/> ASL-003 120 | <input type="checkbox"/> ASL-004 123 |
| <input type="checkbox"/> ASL-005 107 | <input type="checkbox"/> ASL-006 106 |
| <input type="checkbox"/> ASL-007 145 | <input type="checkbox"/> ASL-008 129 |
| <input type="checkbox"/> ASL-009 140 | <input type="checkbox"/> ASL-011 135 |
| <input type="checkbox"/> ASL-012 133 | <input type="checkbox"/> ASL-013 111 |
| <input type="checkbox"/> ASL-014 144 | <input type="checkbox"/> ASL-016 104 |
| <input type="checkbox"/> ASL-017 147 | <input type="checkbox"/> ASL-018 125 |
| <input type="checkbox"/> ASL-019 126 | <input type="checkbox"/> ASL-020 128 |
| <input type="checkbox"/> ASL-021 130 | <input type="checkbox"/> ASL-022 119 |
| <input type="checkbox"/> ASL-024 117 | <input type="checkbox"/> ASL-025 138 |
| <input type="checkbox"/> ASL-028 110 | <input type="checkbox"/> ASL-031 108 |
| <input type="checkbox"/> ASL-033 103 | <input type="checkbox"/> ASL-034 102 |
| <input type="checkbox"/> ASL-035 101 | <input type="checkbox"/> ASL-036 105 |
| <input type="checkbox"/> ASL-038 127 | <input type="checkbox"/> ASL-039 143 |
| <input type="checkbox"/> ASL-040 124 | <input type="checkbox"/> ASL-042 146 |
| <input type="checkbox"/> ASL-043 115 | <input type="checkbox"/> ASL-055 142 |
| <input type="checkbox"/> ASL-056 131 | <input type="checkbox"/> ASL-057 132 |

**CCT Options**

<b>CCT</b>	3000K/3500k/4000K/5000K
------------	-------------------------

## Options

Size	Dimensions	Wattage	Voltage	Lumens
C2125-22	L:22" H:3" W:19" MH:59"	40	DV (120V-277V (non dimming))	5200
C2125-42	L:42" H:3" W:37" MH:59"	80	DV (120V-277V (non dimming))	10400
C2125-63	L:63" H:3" W:56" MH:59"	120	DV (120V-277V (non dimming))	15600

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)