



**Properties**

<b>Base Construction</b>	Aluminum
<b>Lens</b>	Polycarbonate
<b>Application</b>	Pendant
<b>Location</b>	Dry
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED

**Standard Selection**

<b>Voltage</b>	120V-277V (non dimming)
<b>Finish</b>	White
<b>CCT</b>	4000K

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

<b>CCT</b>	3000K/4000K/5000K
------------	-------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
C2130-12	D:11.8" H:0.9" MH:59"	15	DV (120V-277V (non dimming))	1950
C2130-16	D:15.7" H:0.9" MH:59"	20	DV (120V-277V (non dimming))	2600
C2130-20	D:19.7" H:0.9" MH:59"	30	DV (120V-277V (non dimming))	3900
C2130-35	D:35.4" H:0.9" MH:59"	90	DV (120V-277V (non dimming))	11700
C2130-24	D:23.6" H:0.9" MH:59"	40	DV (120V-277V (non dimming))	5200

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)