C2134P
Pendant



Properties

Base Construction	Aluminum
Lens	Polycarbonate
Application	Pendant
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	120

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Black
CCT	4000K

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT	3000K/4000K/5000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2134P-24	D:24" H:6" MH:59"	40	TD (120V Triac dimming) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming)	5200
C2134P-35	D:35" H:6" MH:59"	90	TD (120V Triac dimming) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming)	11700
C2134P-47	D:47" H:6" MH:59"	180	TD (120V Triac dimming) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming)	23400

Not seeing what you're looking for?

Contact us!

info@asllighting.com

© Copyright © 2025 ASL Lighting Inc. All rights reserved.

asllighting.com