# C2134P
Pendant



## Properties

| | |
|---|---|
| **Base Construction** | Aluminum |
| **Lens** | Polycarbonate |
| **Application** | Pendant |
| **Location** | Dry |
| **CRI** | 80 |
| **Life Hours** | 50,000 |
| **Light Source** | Integrated LED |
| **Light Direction** | 120 |

## Standard Selection

| | |
|---|---|
| **Voltage** | 120V-277V (non dimming) |
| **Finish** | Black |
| **CCT** | 4000K |

## Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

## CCT Options

| | |
|---|---|
| **CCT** | 3000K/4000K/5000K |

## Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---|---|---|---|---|
| C2134P-24 | D:24" H:6" MH:59" | 40 | TD (120V Triac dimming) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming) | 5200 |
| C2134P-35 | D:35" H:6" MH:59" | 90 | TD (120V Triac dimming) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming) | 11700 |
| C2134P-47 | D:47" H:6" MH:59" | 180 | TD (120V Triac dimming) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming) | 23400 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com

© Copyright © 2025 ASL Lighting Inc. All rights reserved.

asllighting.com