



**Properties**

<b>Base Construction</b>	Aluminum
<b>Lens</b>	Acrylic
<b>Application</b>	Flush Mount
<b>Location</b>	Damp
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED
<b>Light Direction</b>	160

**Standard Selection**

<b>Voltage</b>	120V-277V 0-10 dimming
<b>Finish</b>	Black
<b>CCT</b>	3CCT - 3000K / 3500K / 4000K

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

<b>CCT</b>	3CCT
------------	------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
C2139-14	D:14.2" H:4.6"	15	DVD (120V-277V 0-10 dimming)	1950
C2139-17	D:17.7" H:4.6"	25	DVD (120V-277V 0-10 dimming)	3250
C2139-24	D:23.6" H:4.6"	36	DVD (120V-277V 0-10 dimming)	4680
C2139-32	D:31.5" H:4.6"	50	DVD (120V-277V 0-10 dimming)	6500

Options  
EMG - Emergency

**Not seeing what you're looking for?**  
Contact us!  
[info@asllighting.com](mailto:info@asllighting.com)