



### Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V (non dimming)
Finish	Black/Gold
CCT	3000K

### Finish Options

Black	Bronze
Brushed Nickel	Gold/Brass
ORB	White
Black/Gold	

### CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
CCS36-12	H:12" W:6" E:4"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
CCS36-15	H:15" W:6" E:4"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600

### Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you’re looking for?

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)