



**Properties**

|                          |                |
|--------------------------|----------------|
| <b>Base Construction</b> | Steel          |
| <b>Lens</b>              | Glass          |
| <b>Application</b>       | Over Bed       |
| <b>Location</b>          | Damp           |
| <b>CRI</b>               | 80             |
| <b>Life Hours</b>        | 50,000         |
| <b>Light Source</b>      | Integrated LED |

**Standard Selection**

|                |                        |
|----------------|------------------------|
| <b>Voltage</b> | 120V-277V 0-10 dimming |
| <b>Finish</b>  | Bronze                 |
| <b>CCT</b>     | 3500k                  |

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

|            |                         |
|------------|-------------------------|
| <b>CCT</b> | 2700K/3000K/3500k/4000K |
|------------|-------------------------|

**Options**

| Size     | Dimensions      | Wattage  | Voltage  | Lumens         |
|----------|-----------------|----------|--|----------------|
| CCV32-24 | H:6" L:24" E:4" | 20/24/30 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3120/3900 |
| CCV32-36 | H:6" L:36" E:4" | 20/30/40 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3900/5200 |
| CCV32-48 | H:6" L:48" E:4" | 30/46/55 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3900/5980/7150 |

**Options**

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!  
[info@asllighting.com](mailto:info@asllighting.com)