



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Pendant
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
CCT	3000K

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT	2700K/3000K/3500k/4000K
-----	-------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
CVBH-22	L:22" H:4.8" W:2.75" MH:60"	11/15/22	TD (120V Triac dimming) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming)	1430/1950/2860
CVBH-34	L:34" H:4.8" W:2.75" MH:60"	18/25	TD (120V Triac dimming) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming)	2340/3250
CVBH-46	L:46" H:4.8" W:2.75" MH:60"	22/30/40	TD (120V Triac dimming) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming)	2860/3900/5200

Not seeing what you're looking for?

Contact us!

info@asllighting.com