



**Properties**

Base Construction	Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

**Standard Selection**

Voltage	120V (non dimming)
Finish	Brushed Nickel
CCT	3000K

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
DOV-27	L:26.75" H:6" E:4.25"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
DOV-39	L:39" H:6" E:4.25"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
DOV-51	L:51" H:6" E:4.25"	20/30/40	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) ND (120V (non dimming)) / TD (120V Triac dimming)	2600/3900/5200

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)