



Properties

| | |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens | Polycarbonate |
| Application | Flush Mount |
| Location | Wet |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish | White |
| CCT | 4000K |

Finish Options

| | |
|--|--|
|  Black |  Brushed Nickel |
|  Gold/Brass |  ORB |
|  White | |

CCT Options

| | |
|-----|-------------------------|
| CCT | 3000K/3500k/4000K/5000K |
|-----|-------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|--------|--------------|----------|--|----------------|
| DRF-11 | D:11" E:3.7" | 10/16/20 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/2080/2600 |

Options

- BBX-Backbox W/ 3/4" Conduit hole
- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming
- PC - Photo Control

Not seeing what you're looking for?

Contact us!

info@asllighting.com