



Properties

Base Construction	Die Cast Aluminum
Lens	Glass
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Bronze
CCT	5000K

Finish Options

 Black	 Bronze
 Brushed Nickel	 Gold/Brass
 ORB	 White

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K/5700K
-----	-------------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
DSKD-14	H:9" W:14.12" E:11.25"	12/24/36/48/60/72	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1560/3120/4680/6240/7800/9360
DSKD-18	W:18.12" H:9" E:13.87"	12/24/36/48/60/72/84/96	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1560/3120/4680/6240/7800/9360/10920/12480

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!
info@asllighting.com