



**Properties**

<b>Base Construction</b>	Die Cast Aluminum
<b>Lens</b>	Glass
<b>Application</b>	Sconce
<b>Location</b>	Wet
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED

**Standard Selection**

<b>Voltage</b>	120V-277V (non dimming)
<b>Finish</b>	Bronze
<b>CCT</b>	5000K

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

<b>CCT</b>	2700K/3000K/3500k/4000K/5000K/5700K
------------	-------------------------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
DSKD-14	H:9" W:14.12" E:11.25"	12/24/36/48/60/72	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1560/3120/4680/6240/7800/9360
DSKD-18	W:18.12" H:9" E:13.87"	12/24/36/48/60/72/84/96	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) ND (120V (non dimming)) / TD (120V Triac dimming)	1560/3120/4680/6240/7800/9360/10920/12480

**Options**

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)