



Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Acrylic           |
| Application       | Flush Mount       |
| Location          | Damp              |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

Standard Selection

|         |                    |
|---------|--------------------|
| Voltage | 120V Triac dimming |
| Finish  | Brushed Nickel     |
| CCT     | 3000K              |

Finish Options

|  |  |
|--|--|
|  Black          |  Bronze     |
|  Brushed Nickel |  Gold/Brass |
|  ORB          |  White    |

CCT Options

|     |                             |
|-----|-----------------------------|
| CCT | 2700K/3000K/5000K/3CCT/5CCT |
|-----|-----------------------------|

Options

| Size   | Dimensions     | Wattage  | Voltage  | Lumens         |
|--------|----------------|----------|--|----------------|
| EOI-12 | D:12.5" H:3.8" | 13/18/25 | TD (120V Triac dimming) / DV (120V-277V (non dimming))   | 1690/2340/3250 |
| EOI-15 | D:15" H:3.8"   | 15/23/30 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/2990/3900 |
| EOI-16 | D:16.6" H:4.1" | 15/20/28 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/2600/3640 |
| EOI-18 | D:18.4" H:4.1" | 15/25/35 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3250/4550 |

Options

- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)