



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
CCT	3000K

Finish Options

 Black	 Bronze
 Brushed Nickel	 Gold/Brass
 ORB	 White

CCT Options

CCT	2700K/3000K/5000K/3CCT/5CCT
-----	-----------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
HCLT-15	W:15.3" H:4.3" L:15.3"	12/18/25	ND (120V (non dimming)) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming)	1560/2340/3250
HCLT-19	W:19.3" H:3.8" L:19.3"	15/25/35	ND (120V (non dimming)) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming)	1950/3250/4550

Options

- BBX-Backbox W/ 3/4" Conduit hole
- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com