



### Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Acrylic           |
| Application       | Flush Mount       |
| Location          | Dry               |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Brushed Nickel          |
| CCT     | 3000K                   |

### Finish Options

|  |  |
|--|--|
|  Black          |  Bronze     |
|  Brushed Nickel |  Gold/Brass |
|  ORB          |  White    |

### CCT Options

|     |                             |
|-----|-----------------------------|
| CCT | 2700K/3000K/5000K/3CCT/5CCT |
|-----|-----------------------------|

### Options

| Size   | Dimensions     | Wattage  | Voltage  | Lumens         |
|--------|----------------|----------|--|----------------|
| HDE-15 | D:14.8" H:4.6" | 15/23/30 | ND (120V (non dimming)) / DV (120V-277V (non dimming))<br>DVD (120V-277V 0-10 dimming) | 1950/2990/3900 |
| HDE-18 | D:17.8" H:4.8" | 15/25/35 | ND (120V (non dimming)) / DV (120V-277V (non dimming))<br>DVD (120V-277V 0-10 dimming) | 1950/3250/4550 |

### Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)