





## **Properties**

Base Construction	Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

## **Standard Selection**

Voltage	120V Triac aimming
Finish	Brushed Nickel
ССТ	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

## **Finish Options**



## **CCT Options**

ССТ	2700K/3000K/3500k/4000K/5000K/5CCT
-----	------------------------------------

Options				
Size	Dimensions	Wattage	Voltage	Lumens
HDT-10	D:10" H:2.3"	10/15/20	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)  ND (120V (non dimming)) / TD (120V Triac dimming)	1300/1950/2600
HDT-12	D:12" H:2.3"	10/15/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/3250
HDT-14	D:14" H:2.3"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
HDT-16	D:16" H:2.3"	15/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/3900
HDT-18	D:18" H:2.3"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
HDT-24	D:24.1" H:5"	25/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/3900/5200
HDT-20	D:20.5" H:5"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200
HDT-28	L:28.3" H:4.4" W:14"	35	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	4550
HDT-32	L:32.3" H:4.4" W:18"	46	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	5980

Options

BBX-Backbox W/ ¾" Conduit hole
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us! info@asllighting.com

© Copyright © 2024 ASL Lighting Inc. All rights reserved.

asllighting.com