# HDZ
Overbed

## Properties

| | |
|---|---|
| **Base Construction** | Steel |
| **Lens** | Acrylic |
| **Application** | Over Bed |
| **Location** | Damp |
| **CRI** | 80 |
| **Life Hours** | 50,000 |
| **Light Source** | Integrated LED |
| **Light Direction** | UP & DOWN WITH 4WAY PULL CHAIN |

## Standard Selection

| | |
|---|---|
| **Voltage** | 120V-277V 0-10 dimming |
| **Finish** | Brushed Nickel |
| **CCT** | 3500k |

## Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

## CCT Options

| | |
|---|---|
| **CCT** | 2700K/3000K/3500k/4000K |

## Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---|---|---|---|---|
| HDZ-13 | H:5" L:13" E:5" | 15/20 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/2600 |
| HDZ-26 | H:5" L:26.5" E:5" | 20/24/30 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3120/3900 |
| HDZ-38 | H:5" L:38.5" E:5" | 20/30/40 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3900/5200 |
| HDZ-50 | H:5" L:50.5" E:5" | 30/46/55 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3900/5980/7150 |

### Options

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

### Not seeing what you're looking for?

Contact us!

info@asllighting.com

© Copyright © 2025 ASL Lighting Inc. All rights reserved.