



**Properties**

|                          |                   |
|--------------------------|-------------------|
| <b>Base Construction</b> | Cold-rolled Steel |
| <b>Lens</b>              | Acrylic           |
| <b>Application</b>       | Flush Mount       |
| <b>Location</b>          | Damp              |
| <b>CRI</b>               | 80                |
| <b>Life Hours</b>        | 50,000            |
| <b>Light Source</b>      | Integrated LED    |

**Standard Selection**

|                |                         |
|----------------|-------------------------|
| <b>Voltage</b> | 120V-277V (non dimming) |
| <b>Finish</b>  | White                   |
| <b>CCT</b>     | 3000K                   |

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

|            |                             |
|------------|-----------------------------|
| <b>CCT</b> | 2700K/3000K/5000K/3CCT/5CCT |
|------------|-----------------------------|

**Options**

| Size    | Dimensions   | Wattage  | Voltage  | Lumens         |
|---------|--------------|----------|--|----------------|
| HORD-16 | D:16" H:4.6" | 15/20/28 | ND (120V (non dimming)) / DV (120V-277V (non dimming))<br>DVD (120V-277V 0-10 dimming) | 1950/2600/3640 |

**Options**

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!  
[info@asllighting.com](mailto:info@asllighting.com)