




Properties

Base Construction	Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V Triac dimming
Finish	Brushed Nickel
CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

Finish Options

 Black	 Bronze
 Brushed Nickel	 Gold/Brass
 ORB	 White

CCT Options

CCT	5CCT
-----	------

Options

Size	Dimensions	Wattage	Voltage	Lumens
HST-11	W:11.5" H:3.75" L:11.5"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
HST-14	W:14.25" H:4" L:14.25"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250
HST-19	W:19.25" H:5" L:19.25"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!
info@asllighting.com