



Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Seeded Glass      |
| Application       | Lantern           |
| Location          | Wet               |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

Standard Selection

|         |                    |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish  | Black              |
| CCT     | 3000K              |

Finish Options

|  |  |
|--|--|
|  Black          |  Bronze     |
|  Brushed Nickel |  Gold/Brass |
|  ORB          |  White    |

CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

Options

| Size    | Dimensions            | Wattage | Voltage   | Lumens    |
|---------|-----------------------|---------|---|-----------|
| LAGA-10 | H:10.8" W:7.3" E:8.5" | 10/15   | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) | 1300/1950 |

Options

PC - Photo Control

Not seeing what you're looking for?

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)