



Properties

Base Construction	Polycarbonate
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V Triac dimming
Finish	White
CCT	3000K

Finish Options

 Black	 Bronze
 Brushed Nickel	 Gold/Brass
 ORB	 White

CCT Options

CCT	2700K/3000K/4000K/5000K/3CCT/5CCT
-----	-----------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
MASB-7	D:7.1" H:0.55"	12	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1560
MASB-9	D:8.86" H:0.55"	18	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) ND (120V (non dimming)) / TD (120V Triac dimming)	2340
MASB-12	D:11.82" H:0.55"	24	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3120

Not seeing what you're looking for?
Contact us!
info@asllighting.com