









## **Properties**

| Base Construction | Steel          |
|-------------------|----------------|
| Lens              | Acrylic        |
| Application       | Address        |
| Location          | Damp           |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

## **Standard Selection**

| Voltage | 120V (non dimming) |
|---------|--------------------|
| Finish  | Black              |
| ССТ     | 3000K              |
|         |                    |

## **Finish Options**

| Black      | Brushed Nickel |
|------------|----------------|
| Gold/Brass | ORB            |

## **CCT Options**

White

2700K/3000K/3500k/4000K CCT

| Options  |                 |          |  |                |
|----------|-----------------|----------|--|----------------|
| Size     | Dimensions      | Wattage  | Voltage  | Lumens         |
| NB123-8  | H:8" W:5" E:4"  | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |
| NB123-14 | H:14" W:6" E:4" | 10/15/25 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/3250 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com

© Copyright © 2025 ASL Lighting Inc. All rights reserved.



asllighting.com