



### Properties

|                   |                                      |
|-------------------|--------------------------------------|
| Base Construction | Aluminum Extrusion/Cold-rolled Steel |
| Lens              | Glass                                |
| Application       | Address                              |
| Location          | Damp                                 |
| CRI               | 80                                   |
| Life Hours        | 50,000                               |
| Light Source      | Integrated LED                       |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Black/Maple             |
| CCT     | 3000K                   |

### Finish Options

|            |                |
|------------|----------------|
| Bronze     | Brushed Nickel |
| Gold/Brass | ORB            |
| White      | Black/Maple    |

### CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

### Options

| Size     | Dimensions          | Wattage | Voltage                                                                                                          | Lumens |
|----------|---------------------|---------|------------------------------------------------------------------------------------------------------------------|--------|
| NB149-16 | H:15.8" W:6" E:3.8" | 12      | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1560   |

Not seeing what you're looking for?  
Contact us!  
[info@asllighting.com](mailto:info@asllighting.com)