



**Properties**

Base Construction	Steel
Lens	Fabric
Application	Over Bed
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	UP & DOWN WITH 4WAY PULL CHAIN

**Standard Selection**

Voltage	120V-277V 0-10 dimming
Finish	Brushed Nickel
CCT	3500k

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**Fabric Finish**

- Chocolate Linen
- Grey Linen
- Jute Linen
- White Linen

**CCT Options**

CCT	2700K/3000K/3500k/4000K
-----	-------------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
OBCB-36	H:7" L:36" E:5"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200
OBCB-48	H:7" L:48" E:5"	30/46/55	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/5980/7150

**Options**

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)