



### Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Over Bed
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	UP & DOWN WITH 4WAY PULL CHAIN

### Standard Selection

Voltage	120V-277V (non dimming)
Finish	BRUSHED ALUMINUM / BLACK
CCT	3CCT - 3000K / 3500K / 4000K

### Finish Options

Black	Bronze
Brushed Nickel	Gold/Brass
ORB	White
BRUSHED ALUMINUM / BLACK	

### CCT Options

CCT	3CCT
-----	------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
OVBJH-23	H:4.3" L:23.8" E:2.3"	30	DV (120V-277V (non dimming))	3900
OVBJH-35	H:4.3" L:35.8" E:2.3"	34	DV (120V-277V (non dimming))	4420
OVBJH-47	H:4.3" L:47.8" E:2.3"	40	DV (120V-277V (non dimming))	5200

### Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)