



Properties

| | |
|--------------------------|----------------|
| Base Construction | Steel |
| Lens | Fabric/Acrylic |
| Application | Flush Mount |
| Location | Dry |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|----------------|--------------------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | Brushed Nickel Trim With Fabric Lens |
| CCT | 3000K |

Finish Options

- Brushed Nickel Trim With Fabric Lens

Fabric Finish

- White Linen

CCT Options

| | |
|------------|-----------------------------|
| CCT | 2700K/3000K/5000K/3CCT/5CCT |
|------------|-----------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|----------|--------------|----------|--|----------------|
| RFMHA-17 | D:17" H:5.4" | 15/24 | DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) ND (120V (non dimming)) | 1950/3120 |
| RFMHA-20 | D:20" H:5.9" | 15/25/35 | ND (120V (non dimming)) / DV (120V-277V (non dimming)) DVD (120V-277V 0-10 dimming) | 1950/3250/4550 |

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com