




Properties

| | |
|-------------------|----------------|
| Base Construction | Steel |
| Lens | Fabric/Acrylic |
| Application | Flush Mount |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--|
| Voltage | 120V Triac dimming |
| Finish | N/A |
| CCT | 5CCT - 2700K / 3000K / 3500K / 4000K / 5000K |

Fabric Finish

| | |
|---|---|
|  Black Linen |  Chocolate Linen |
|  Grey Linen |  Jute Linen |
|  White Linen | |

CCT Options

| | |
|-----|------------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K/5CCT |
|-----|------------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|---------------|----------|--|----------------|
| RFNA-12 | D:12" H:4" | 10/15/25 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/3250 |
| RFNA-15 | D:15" H:4" | 10/15/25 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/3250 |
| RFNA-19 | D:19" H:5.25" | 15/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3250/3900 |
| RFNA-24 | D:24" H:8" | 15/25/35 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3250/4550 |
| RFNA-30 | D:30" H:8" | 25/35/40 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3250/4550/5200 |
| RFNA-36 | D:36" H:8" | 35/40/50 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 4550/5200/6500 |

Options

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com

