



Properties

Base Construction	Steel
Lens	Fabric/Acrylic
Application	Pendant
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V Triac dimming
Finish	Brushed Nickel
CCT	3000K

Fabric Finish

<input type="checkbox"/> Black Linen	<input type="checkbox"/> Chocolate Linen
<input type="checkbox"/> Grey Linen	<input type="checkbox"/> Jute Linen
<input type="checkbox"/> White Linen	

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K/5CCT
------------	------------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
RFNAP-12	D:12" H:4" MH:6'	10/15/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/3250
RFNAP-15	D:15" H:4" MH:6'	10/15/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/3250
RFNAP-19	D:19" H:5.25" MH:6'	15/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/3900
RFNAP-24	D:24" H:8" MH:6'	15/25/35	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/4550
RFNAP-30	D:30" H:8" MH:6'	25/35/40	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/4550/5200
RFNAP-36	D:36" H:8" MH:6'	35/40/50	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	4550/5200/6500

Options

EMG – Emergency
 OS - Occupancy Sensor
 OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@aslighting.com

