



Properties

Base Construction	Steel
Lens	Fabric/Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V Triac dimming
CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

Fabric Finish

<input type="checkbox"/> Black Linen	<input type="checkbox"/> Chocolate Linen
<input type="checkbox"/> Grey Linen	<input type="checkbox"/> Jute Linen
<input type="checkbox"/> White Linen	

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K/5CCT
------------	------------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
RFNF-12	D:12.25" H:4"	10/15/25	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) ND (120V (non dimming)) / TD (120V Triac dimming)	1300/1950/3250
RFNF-15	D:15" H:4"	10/15/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/3250
RFNF-19	D:19.25" H:5.25"	15/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/3900
RFNF-24	D:24" H:8"	15/25/35	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/4550
RFNF-30	D:30" H:8"	25/35/40	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/4550/5200
RFNF-36	D:36" H:8"	35/40/50	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	4550/5200/6500

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com

