



Properties

| | |
|--------------------------|----------------|
| Base Construction | Steel |
| Lens | Fabric/Acrylic |
| Application | Flush Mount |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|----------------|--|
| Voltage | 120V Triac dimming |
| CCT | 5CCT - 2700K / 3000K / 3500K / 4000K / 5000K |

Fabric Finish

- Black Linen
- Chocolate Linen
- Grey Linen
- Jute Linen
- White Linen

CCT Options

| | |
|------------|------------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K/5CCT |
|------------|------------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|------------------|----------|--|----------------|
| RFNF-12 | D:12.25" H:4" | 10/15/25 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/3250 |
| RFNF-15 | D:15" H:4" | 10/15/25 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/3250 |
| RFNF-19 | D:19.25" H:5.25" | 15/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3250/3900 |
| RFNF-24 | D:24" H:8" | 15/25/35 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3250/4550 |
| RFNF-30 | D:30" H:8" | 25/35/40 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3250/4550/5200 |
| RFNF-36 | D:36" H:8" | 35/40/50 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 4550/5200/6500 |

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com

